

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		204	221		252
4		221	256		300
6		278	321		360
10		336	400		524
16	231	388	444		568
25	287	401	534	626	673
35	359	513	731	809	921
50	457	694	945	1078	1214
70	581	880	1268	1469	1646
95	710	1137	1610	1860	2171
120	850	1401	1997	2332	2656
150	1013	1715	2474	2720	3209
185	1228	2093	3060	3441	4043
240	1526	2648	3959	4386	5228
300	1855	3257	4896	5440	6462
400	2395	4269	6214	6902	8309
500	2905	5928	8348	9832	11025
630	3585	7292	10613	12047	14472
800	4461				
1000	5440				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring	
- 2 x 16 & above	30%
- 3 x 16 & 3.5CX25 & above	30%
- 4 x 10 & above	30%
- For Single core 95 & above	30%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
d) HR PVC Insulation	17.5%
e) HR PVC Inner Sheath	7.5%
f) HR PVC Outer Sheath	7.5%
g) Oxygen Index (FR)	4%
h) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
	Armoured			
	Power (Al.)			
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
	Power Single Core (Al.)			
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		128	171		206
6		184	231		262
10		253	303		366
16	131	262	352		472
25	156	327	465	596	631
35	204	439	663	717	794
50	278	576	813	954	1047
70	378	785	1146	1318	1500
95	493	1019	1522	1744	2012
120	615	1267	1905	2211	2540
150	770	1585	2395	2674	3162
185	944	1933	2923	3344	3891
240	1200	2470	3759	4263	4980
300	1489	3056	4655	5289	6199
400	1970	4033	6131	6765	8169
500	2441	5809	8181	9635	10805
630	3063	7146	10401	11806	14183
800	3867				
1000	4830				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
c) HR PVC Insulation	17.5%
d) HR PVC Inner Sheath	7.5%
e) HR PVC Outer Sheath	7.5%
f) Oxygen Index (FR)	4%
g) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		473	655	851	1135	1411	1547
6		670	949	1231	1683	2030	2366
10		1069	1523	2016	2667		
16	925	1512	2262	2973	3974		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY		Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	242	342	14	1139	1880
3	308	452	16	1302	2125
4	386	585	19	1544	2499
5	491	724	24	1931	3148
6	596	850	27	2189	3586
7	619	989	30	2441	4313
8	704	1125	37	3166	5038
10	881	1353	44	3698	5884
12	993	1605	61	5444	8530

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
1.5 sq.mm - 12 core & above	18%
2.5 sq.mm - 9 core & above	18%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.5%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
2 to 4 Core	7.5%	9%	22.5%	22.5%
5 to 10 Core	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18%	18%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core
	2XY	2XY	2XY	2XY
4		415	605	799
6		612	900	1189
10		1013	1484	1987
16	801	1485	2234	2945

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	186	284	14	1061	1818
3	254	400	16	1257	2071
4	333	534	19	1494	2452
5	434	668	24	1864	3098
6	521	784	27	2089	3456
7	554	928	30	2480	4097
8	632	1057	37	3212	4913
10	803	1296	44	3757	5856
12	918	1551	61	5496	8060

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES) :

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D OXYGEN INDEX (FR)	4%
E) HR PVC Insulation	17.5%
HR PVC I/S & O/S	7.5% Each
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
G) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
	Unarmd			
2 - 4	7.5%	9%	22.5%	22.5%
5 - 10	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18%	18%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	1424	2355	3536	4290	4703	7256
35	1945	3478	5101	5841	6749	10000
50	2723	4695	6882	8103	9198	13750
70	3752	6975	9980	11653	13366	21625
95	5009		13968	16191	18255	
120	6279		17235	20537	22981	
150	7801		21212	24572	28440	
185	9595		26865	31405	35580	
240	12376		35040	40476	46521	
300	15413		44756	51166	59038	
400	20483		57882	64796	80631	
500	25504					
630	32062					
800	40603					
1000	50619					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	1341	2292	3454	4202	4607	
35	1862	3402	5013	5739	6639	
50	2644	4610	6784	7993	9076	
70	3692	6865	9858	11523	13221	
95	4783		13826	16037	18095	
120	6033		17078	20356	22803	
150	7544		21051	24378	28242	
185	9297		26656	31178	35353	
240	12036					
300	15032					
400	20030					
500	25021					
630	31518					
800	39999					
1000	49980					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

Size in Sq.mm.	(Rate in Rs. Per Mtr.)					
	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		1735				
50		2089				
70	2274	2537				
95	2700	3028	3938	3902	4946	
120	3272	3554	4264	4351	5538	
150	3837	4157	5116	5220	6512	7046
185	4525	4875	5632	5748	7098	7652
240	5791	6200	6739	6875	8257	8740
300	6651	7044	8019	8185	9442	10392
400	8588	8975	9852	10052	11309	11890

EXTRA FOR SPECIAL CONSTRUCTION:

1) Extruded PVC Inner Sheath	4.5%	
2) Pressure Extruded PVC Innersheath	19.5%	
3) Round Wire Armouring - Up to 11 KV (E)	30%	
11 KV (UE) & Above	33%	
4) FRLS PVC Inner Sheath	7.5%	
5) FRLS PVC Outer Sheath	7.5%	
6) FR Sheath with Oxygen Index	4.5%	

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable confirming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	2025	2350	2120	2455	2403	2792	2479	2867	2980	3441	3413	3940
300	2395	2747	2479	2825	2776	3181	2852	3271	3385	4102	3643	4415
400	3026	3347	3075	3397	3411	3785	3499	3865	4038	4752	4272	5035
500	3630	4027	3653	4065	4012	4699	4095	4801	4670	5466	4867	5700
630	4379	4877	4393	4892	4767	5576	4858	5674	5489	6388	5715	6649
800	5326	6162	5346	6195	5754	6657	5859	6774	6517	7514	6800	7836
1000	6464	7457	6475	7457	6932	7952	7023	8080	7745	9327	8325	10065

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	11.5%
2) FRLS PVC Outer Sheath	7.5%
3) Oxygen Index	4.5%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB Brand Aluminium Conductor, XLPE Insulated, flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
1 Core x 120	644
1 Core x 150	749
1 Core x 185	920
1 Core x 240	1104
1 Core x 300	1393
1 Core x 400	1682
1 Core x 500	2235
1 Core x 630	2734

POLYCAB Brand Sector Shaped Aluminium Conductor, XLPE Insulated, innersheath of PVC tape, Galvanised steel wire / flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
3 Core x 120	1640
3 Core x 150	2011
3 Core x 185	2398
3 Core x 240	3060
3 Core x 300	3720
3 Core x 400	4635

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.