

POLYCAB IDEAS. CONNECTED.	POLYCAB INDIA LIMITED
PCC LP No. 06/2026-27 Dtd : 21st October 2026	
List of Products Covered in Our PCC LP	
Aluminium Armoured / Unarmoured Cables	
Copper Armoured / Unarmoured Cables	
HT Cables	
1.9 KV / 3.3 KV Cables for Solar	
Instrumentation Cables	
Rubber Cables	
JFTC Unarmoured/Armoured Cables & Telephone Dry Armoured Cables	
RS 485 Cables	

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		220	236		261
4		236	278		309
6		297	346		387
10		342	409		535
16	237	398	455		580
25	296	410	545	640	688
35	368	525	746	826	941
50	469	709	966	1102	1241
70	596	903	1297	1501	1683
95	729	1168	1668	1902	2219
120	873	1439	2041	2384	2716
150	1040	1761	2528	2780	3281
185	1262	2150	3128	3535	4133
240	1568	2720	4047	4506	5345
300	1906	3346	5005	5589	6606
400	2461	4386	6351	7092	8494
500	2984	6090	8534	10050	11270
630	3684	7490	10849	12314	14794
800	4582				
1000	5587				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring	
- 2 x 16 & above	30%
- 3 x 16 & 3.5CX25 & above	30%
- 4 x 10 & above	30%
- For Single core 95 & above	30%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
d) HR PVC Insulation	17.5%
e) HR PVC Inner Sheath	7.5%
f) HR PVC Outer Sheath	7.5%
g) Oxygen Index (FR)	4%
h) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		131	175		211
6		189	237		270
10		259	310		374
16	134	269	360		483
25	161	334	475	610	645
35	209	450	678	733	811
50	285	589	831	975	1070
70	388	806	1172	1348	1534
95	507	1046	1562	1784	2057
120	631	1301	1947	2260	2597
150	791	1629	2449	2733	3232
185	969	1985	2988	3436	3978
240	1232	2537	3844	4380	5091
300	1529	3139	4758	5434	6338
400	2024	4143	6267	6950	8351
500	2507	5966	8363	9849	11045
630	3148	7340	10632	12069	14498
800	3972				
1000	4962				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
c) HR PVC Insulation	17.5%
d) HR PVC Inner Sheath	7.5%
e) HR PVC Outer Sheath	7.5%
f) Oxygen Index (FR)	4%
g) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
Power (Al.)				
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
Power Single Core (Al.)				
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		565	784	1020	1423	1689	1938
6		804	1135	1476	2115	2542	2965
10		1304	1857	2458	3253		
16	1134	1845	2759	3625	4846		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY			Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.			1.5 Sq.mm.	2.5 Sq.mm.
2	291	410		14	1369	2262
3	371	545		16	1566	2556
4	466	702		19	1856	3003
5	592	872		24	2322	3783
6	715	1023		27	2632	4312
7	745	1190		30	2933	5185
8	847	1372		37	3806	6054
10	1061	1629		44	4444	7072
12	1193	1929		61	6545	10254

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
1.5 sq.mm - 12 core & above	18%
2.5 sq.mm - 9 core & above	18%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.5%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH			
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath		
		Armoured				
2 to 4 Core	7.5%	9%	22.5%	22.5%		
5 to 10 Core	7.5%	6%	22.5%	22.5%		
12 & Above	7.5%	6%	18%	18%		

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core		3 Core	4 Core	
	2XY	2XY		2XY	2XY	
4		494		721	951	
6		728		1071	1415	
10		1235		1810	2424	
16	1000	1811		2725	3592	

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	221	338	14	1262	2165
3	303	476	16	1497	2466
4	397	636	19	1778	2920
5	517	795	24	2220	3686
6	620	933	27	2488	4115
7	659	1106	30	2953	4878
8	759	1259	37	3822	5847
10	956	1542	44	4472	6970
12	1094	1847	61	6544	9595

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES) :

A) Tinning	3%	
B) Stranding (Upto 6 SQ.MM)	4%	
C) Extruded Innersheath	4%	
D OXYGEN INDEX (FR)	4%	
E) HR PVC Insulation	17.5%	
HR PVC I/S & O/S	7.5% Each	
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%	
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%	
G) PVC Insulated Cables	15%	

FRLS Loading Factor- Control Cable			LSZH		
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath	
	Unarmd				
2 - 4	7.5%	9%	22.5%	22.5%	
5 - 10	7.5%	6%	22.5%	22.5%	
12 & Above	7.5%	6%	18%	18%	

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Glavanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	1796	2956	4437	5384	5902	9105
35	2452	4364	6401	7330	8469	12549
50	3434	5891	8637	10169	11542	17256
70	4732	8752	12525	14623	16773	27137
95	6460		17936	20780	23697	
120	8097		22120	26358	29496	
150	10062		27224	31536	36501	
185	12374		34480	40307	45666	
240	15960		44972	51947	59707	
300	19878		57441	65689	75772	
400	26416		74287	83161	103484	
500	32892					
630	41350					
800	52365					
1000	65283					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	1692	2876	4334	5272	5781	
35	2348	4269	6291	7202	8332	
50	3335	5784	8514	10031	11390	
70	4656	8616	12370	14461	16592	
95	6168		17754	20583	23490	
120	7781		21919	26124	29267	
150	9730		27017	31287	36248	
185	11991		34210	40016	45374	
240	15523					
300	19385					
400	25833					
500	32270					
630	40649					
800	51586					
1000	64460					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

	(Rate in Rs. Per Mtr.)					
Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		1773				
50		2135				
70	2325	2593				
95	2760	3095	4025	3990	5098	
120	3345	3633	4359	4448	5717	
150	3922	4250	5229	5336	6656	7203
185	4626	4984	5758	5877	7332	7905
240	5919	6339	6887	7028	8440	8936
300	6799	7201	8198	8367	9652	10623
400	8780	9174	10070	10274	11561	12154

EXTRA FOR SPECIAL CONSTRUCTION:

1) Extruded PVC Inner Sheath	4.5%	
2) Pressure Extruded PVC Innersheath	19.5%	
3) Round Wire Armouring - Up to 11 KV (E)	30%	
11 KV (UE) & Above	33%	
4) FRLS PVC Inner Sheath	7.5%	
5) FRLS PVC Outer Sheath	7.5%	
6) FR Sheath with Oxygen Index	4.5%	

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable confirming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	2082	2415	2180	2523	2469	2868	2547	2946	3061	3535	3505	4047
300	2461	2821	2547	2902	2852	3266	2930	3360	3477	4213	3743	4534
400	3109	3438	3159	3490	3503	3889	3594	3970	4148	4882	4387	5172
500	3728	4136	3752	4176	4121	4827	4207	4931	4796	5614	4999	5856
630	4498	5010	4513	5025	4896	5727	4990	5828	5639	6562	5870	6829
800	5471	6329	5490	6363	5911	6838	6018	6958	6694	7718	6984	8049
1000	6640	7660	6651	7660	7120	8169	7214	8300	7955	9580	8551	10339

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	11.5%
2) FRLS PVC Outer Sheath	7.5%
3) Oxygen Index	4.5%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB Brand Aluminium Conductor, XLPE Insulated, flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
1 Core x 120	676
1 Core x 150	785
1 Core x 185	965
1 Core x 240	1157
1 Core x 300	1461
1 Core x 400	1763
1 Core x 500	2344
1 Core x 630	2867

POLYCAB Brand Sector Shaped Aluminium Conductor, XLPE Insulated, innersheath of PVC tape, Galvanised steel wire / flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
3 Core x 120	1721
3 Core x 150	2109
3 Core x 185	2516
3 Core x 240	3210
3 Core x 300	3902
3 Core x 400	4861

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	161	0.75	186	1	209	1.5	251	2.5	386
CORE	3	0.5	191	0.75	243	1	274	1.5	355	2.5	503
CORE	4	0.5	225	0.75	286	1	332	1.5	412	2.5	656
CORE	5	0.5	301	0.75	374	1	441	1.5	563	2.5	817
CORE	6	0.5	290	0.75	385	1	464	1.5	593	2.5	943
CORE	7	0.5	368	0.75	470	1	568	1.5	737	2.5	1105
CORE	8	0.5	359	0.75	487	1	585	1.5	764	2.5	1202
CORE	10	0.5	434	0.75	609	1	719	1.5	915	2.5	1467
CORE	12	0.5	488	0.75	682	1	826	1.5	1094	2.5	1812
CORE	14	0.5	618	0.75	793	1	993	1.5	1370	2.5	2055
CORE	16	0.5	657	0.75	872	1	1054	1.5	1404	2.5	2219
CORE	19	0.5	761	0.75	1011	1	1282	1.5	1733	2.5	2722
CORE	24	0.5	896	0.75	1257	1	1483	1.5	1939	2.5	3435
PAIR	1	0.5	161	0.75	186	1	209	1.5	251	2.5	386
PAIR	2	0.5	244	0.75	312	1	353	1.5	438	2.5	694
PAIR	3	0.5	302	0.75	398	1	476	1.5	610	2.5	954
PAIR	4	0.5	366	0.75	497	1	598	1.5	774	2.5	1220
PAIR	5	0.5	447	0.75	617	1	729	1.5	931	2.5	1489
PAIR	6	0.5	514	0.75	710	1	858	1.5	1125	2.5	1901
PAIR	7	0.5	621	0.75	810	1	1010	1.5	1385	2.5	2081
PAIR	8	0.5	658	0.75	909	1	1093	1.5	1430	2.5	2265
PAIR	10	0.5	833	0.75	1097	1	1377	1.5	1875	2.5	2874
PAIR	12	0.5	895	0.75	1272	1	1500	1.5	2062	2.5	3460
PAIR	14	0.5	1038	0.75	1439	1	1817	1.5	2533	2.5	3902
PAIR	16	0.5	1183	0.75	1584	1	2054	1.5	2831	2.5	4431
PAIR	19	0.5	1346	0.75	1876	1	2391	1.5	3308	2.5	5192
PAIR	24	0.5	1680	0.75	2415	1	3148	1.5	4025	2.5	6216
TRIAD	1	0.5	199	0.75	244	1	277	1.5	358	2.5	514
TRIAD	2	0.5	347	0.75	453	1	504	1.5	653	2.5	995
TRIAD	3	0.5	501	0.75	630	1	721	1.5	947	2.5	1399
TRIAD	4	0.5	546	0.75	745	1	860	1.5	1115	2.5	1840
TRIAD	5	0.5	698	0.75	927	1	1077	1.5	1456	2.5	2166
TRIAD	6	0.5	804	0.75	1071	1	1267	1.5	1681	2.5	2547
TRIAD	7	0.5	891	0.75	1188	1	1412	1.5	1893	2.5	2900
TRIAD	8	0.5	951	0.75	1296	1	1465	1.5	2019	2.5	3342
TRIAD	10	0.5	1187	0.75	1620	1	1922	1.5	2645	2.5	4081
TRIAD	12	0.5	1349	0.75	1860	1	2251	1.5	3089	2.5	4828
TRIAD	14	0.5	1536	0.75	2127	1	2575	1.5	3548	2.5	5558
TRIAD	16	0.5	1703	0.75	2370	1	2895	1.5	4020	2.5	6303
TRIAD	19	0.5	1963	0.75	2754	1	3370	1.5	4696	2.5	7391
TRIAD	24	0.5	2430	0.75	3446	1	4212	1.5	5912	2.5	9300
QUAD	1	0.5	233	0.75	302	1	341	1.5	448	2.5	674

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	399	0.75	448	1	520	1.5	635	2.5	895
PAIR	3	0.5	513	0.75	571	1	674	1.5	825	2.5	1164
PAIR	4	0.5	614	0.75	703	1	818	1.5	1036	2.5	1434
PAIR	5	0.5	723	0.75	831	1	987	1.5	1212	2.5	1750
PAIR	6	0.5	798	0.75	965	1	1054	1.5	1333	2.5	2037
PAIR	7	0.5	913	0.75	1067	1	1273	1.5	1608	2.5	2319
PAIR	8	0.5	1038	0.75	1180	1	1424	1.5	1823	2.5	2645
PAIR	10	0.5	1225	0.75	1441	1	1735	1.5	2229	2.5	3245
PAIR	12	0.5	1368	0.75	1677	1	1877	1.5	2457	2.5	3713
PAIR	14	0.5	1583	0.75	1885	1	2299	1.5	2971	2.5	4392
PAIR	16	0.5	1781	0.75	2121	1	2578	1.5	3349	2.5	4969
PAIR	19	0.5	2034	0.75	2440	1	2982	1.5	3911	2.5	5809
PAIR	24	0.5	2532	0.75	3066	1	3747	1.5	4932	2.5	7308
TRIAD	2	0.5	494	0.75	568	1	644	1.5	798	2.5	1102
TRIAD	3	0.5	614	0.75	723	1	839	1.5	1063	2.5	1506
TRIAD	4	0.5	750	0.75	899	1	1040	1.5	1305	2.5	1910
TRIAD	5	0.5	888	0.75	1071	1	1259	1.5	1607	2.5	2369
TRIAD	6	0.5	1024	0.75	1225	1	1445	1.5	1882	2.5	2781
TRIAD	7	0.5	1133	0.75	1366	1	1621	1.5	2131	2.5	3159
TRIAD	8	0.5	1268	0.75	1570	1	1843	1.5	2430	2.5	3604
TRIAD	10	0.5	1526	0.75	1899	1	2257	1.5	2983	2.5	4479
TRIAD	12	0.5	1766	0.75	2203	1	2635	1.5	3486	2.5	5251
TRIAD	14	0.5	1985	0.75	2505	1	3026	1.5	4021	2.5	6049
TRIAD	16	0.5	2233	0.75	2824	1	3397	1.5	4548	2.5	6865
TRIAD	19	0.5	2587	0.75	3283	1	3987	1.5	5348	2.5	8041
TRIAD	24	0.5	3245	0.75	4131	1	5025	1.5	6683	2.5	10179

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						884	1300	1807	2588
2 Core	198	318	482	728	1243	1951	2973	4001	5693
3 Core	276	455	695	1049	1801	2765	4267	5889	8413
4 Core	372	598	912	1383	2364	3649	5602	7743	11132
5 Core	487	818	1252						
6 Core	553	894							
7 Core	623	1019							
8 Core	716	1224							
10 Core	912	1520							
12 Core	1073	1795							
14 Core	1243	2083							
16 Core	1411	2368							
19 Core	1711	2782							
24 Core	2178	3533							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	3653	4804	6106	7608	9286	12267	15381	20229	
3 Core	11874	15615	19845	24724	30255	39688	50425	65063	
4 Core	15681	20819	26025	32533	39753	52376	65470	86208	

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR				
0.5	173	269				

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED,G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	227	348	614	1359	2593	4759

POLYCAB BRAND SOLID COPPER CONDUCTOR, POLYTHENE INSULATION, TWISTED PAIRS, LAY-UP, EXTRUDED ST1 GREY PVC INNER SHEATH, SINGLE LAYER GS ROUND WIRE ARMoured, EXT ST1 GREY PVC OUTER SHEATHED TELEPHONE ARMoured CABLE AS PER BSNL GR/WIR-06/03 MAR 2002

SIZE	5 PAIR	10 PAIR	20 PAIR			
0.5	198	379	587			

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	212
	22 AWG	0.32	240
	20 AWG	0.50	258
	18 AWG	0.80	309
	17 AWG	1.00	343
2 Pair	24 AWG	0.205	318
	22 AWG	0.32	351
	20 AWG	0.50	367
	18 AWG	0.80	503
	17 AWG	1.00	563

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	142
	22 AWG	0.32	164
	20 AWG	0.50	181
	18 AWG	0.80	234
	17 AWG	1.00	263
2 Pair	24 AWG	0.205	220
	22 AWG	0.32	263
	20 AWG	0.50	297
	18 AWG	0.80	397
	17 AWG	1.00	454

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	238
	22 AWG	0.32	269
	20 AWG	0.50	288
	18 AWG	0.80	346
	17 AWG	1.00	384
2 Pair	24 AWG	0.205	356
	22 AWG	0.32	393
	20 AWG	0.50	411
	18 AWG	0.80	563
	17 AWG	1.00	631

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	160
	22 AWG	0.32	183
	20 AWG	0.50	203
	18 AWG	0.80	262
	17 AWG	1.00	295
2 Pair	24 AWG	0.205	247
	22 AWG	0.32	295
	20 AWG	0.50	333
	18 AWG	0.80	444
	17 AWG	1.00	509